

JONENG卓能



JONENG卓能

JoNeng Valves Co.,ltd

Add: Shacheng Industrial Zone,
Longwan district, Wenzhou city, China

Tel: 86-577-85809317

Fax: 86-577-85809318

Email: info@jo-neng.com

**YOUR ONE STOP SOLUTION
FOR SANITARY COMPONENTS!**

JONENG VALVES CO.,LTD



Brief Introduction

JoNeng valves is a leading supplier for sanitary stainless steel valves and fittings.

JoNeng valves provides the following sanitary flow control components:

Sanitary valves(butterfly,check,ball,CPM,diaphragm valves...)

Sanitary fittings(elbow,tee,clamp, ferrule,union,cleaing ball,sight glass,filter...)

Sanitary pump(centrifugal,rotary lobe,CIP)

Pipe materials(stainless steel pipe,bar,sheet...)

JoNeng services for food,beverage,dairy,chemical,biopharmaceutical,and etc industries.


JoNeng valves believes in "What we say, what we do". We always believe honesty is the only way leading to long term business relationship. Trying our best for customers and put ourselves into customers' shoes. Making business with us, making friends with us.

JoNeng has been doing business with customers all over the world since 2007. After so many years, JoNeng know more about customers' requirements and offer better services. Our commitment to fine craftsmanship, good quality, fast delivery time, good after-sales work. In long term relationship, good after-sales work is the most important thing for customers. We are so happy that customers never would like to leave us.

Welcome to join with JoNeng!



Certificate



Quality Control



Sanitary Butterfly Valve

Manual, penumatic and electrical operation
Different manual handle: pull handle, gripper handle, steel trigger handle
Actuator type: single action type (air/spring), double action type (air/air)
Valve body and disk are full CNC machined
Valve body: casting or forging to meet different requirements
Material grade: SS304 or SS316L
Gasket: EPDM, silicone, teflon (FDA approved raw material)
Size range: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4", 6", 8", 10"
Standard: 3A, SMS, ISO, DIN, BS, AS1528
Connection: clamp, weld, Male, female, flange, etc



Stop/ Seat Valve

Flow Diversion Valve

Manual and pneumatic operation
Actuator type: single action type (air/spring), double action type (air/air)
Equipped with Definox control box if required
Different body types: 20type, 21 type, 22 type, 30 type, 31 type, 32 type
Gasket: EPDM, silicone, teflon (FDA approved raw material)
Size range: 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4"
Standard: 3A, SMS, ISO, DIN, BS, JIS
Connection: clamp, weld, union, etc
Material grade: SS304 or SS316L



Sanitary Mixproof Valve

Different models: 3-way double seat type, Double seat type, etc
Equipped with Definox control box
Gasket: EPDM, silicone, teflon (FDA approved raw material)
Size range: 1 1/2", 2", 3", 4"
Standard: 3A, SMS, ISO, DIN
Connection: clamp, weld, union, etc
Material grade: SS304 or SS316L
Widely used for food, beverage, dairy, beer, industries



Ball/Diaphragm Valve

Sanitary Ball Valve

Valve body type: straight type, three ways, three pieces, non-retention type, butterfly type, etc

Manual type or Electrical actuator or pneumatic actuator

Actuator type: single action type (air/ spring), double action type (air/air)

The valve ball type: T type, L type, straight type

With cleaning and drainage port

Material: SS304, SS316L

Gasket: EPDM, silicone, teflon (FDA approved raw material)

Size range: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4"

Standard: 3A, SMS, ISO, DIN, BS, AS1528

Connection: clamp , weld, Male, female, flange, etc



Diaphragm Valve

Manual and pneumatic operation

Clean, easy remaintenance, easy operation, no-leaking.

Body: casting or forging materials

Different types: T shape, tank bottom, three way, two way , U types

Gasket: EPDM, EPDM+PTFE (FDA approved raw material)

Size range: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4"

Standard: 3A, ISO, DIN,

Connection: clamp , weld, etc

Material grade: SS304 or SS316L

Application: Pharmacy, beer, food, dairy, beverage, cosmetic, chemical industry



Check/Sampling Valve

Check Valve

Manual operation

Nut type or clamp type

Body: casting or forging materials

Gasket: EPDM, silicone, teflon (FDA approved raw material)

Size range: 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4", 6", 8"

Standard: 3A, SMS, ISO, DIN

Connection: clamp , weld, etc

Material grade: SS304 or SS316L

Our check valves are widely used for food, beverage, dairy, biotech, pharmacy, gas and etc industries.



Sampling Valve

Normal and aseptic sampling valves

Max. pressure: 1000kpa (valve close)

Max. pressure: 500Kpa for silicone (valve open)

1000Kpa for stainless steel part (valve open)

Max. temperature: 130°C

Normally we change the gasket after 100 times sterilization.

Size: 1/4", 1/2", 3/4", 1"

The valve body: SS304 or SS316L

Gasket: Silicone, EPDM



Safety/Constant Pressure Valve

Safety Valve

Ball type body or line type body
Gasket: EPDM, silicone, teflon (FDA approved raw material)
Size range: 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4"
Standard: 3A, SMS, ISO, DIN, BS, JIS
Connection: clamp , weld, union, etc
Material grade: SS304 or SS316L
Our safety valves are widely used for food, beverage, dairy, biotech, pharmacy, gas and etc industries.



CPM Valve

Pneumatic actuated
Max. Pressure: 10 bar
Min. Pressure: 0 bar
Material temperature: -10°C 140°C
Flow range KV, Open: 23m³/h
Flow range KV, low production: 2m³/h
Optional range KV, 15m³/h
Size: 1", 1.5", 2", 2.5"
Material: SS304, 316L



Sanitary Fittings

The blanks of pipe fitting blank are made from forging raw steel. The raw steel is selected without any mistake in Nickel and other chemical component. Then moulded by hydraulic press, shaping, correcting and reshaping.
For union, ferrule, end cap.. we use first class LG ZAMAK CNC for machining. Therefore our CNC parts are exactly correct size without any human error.
For elbow, tee, reducers... After products are finished, we recheck the roundness, thickness uniformity, Ra value, sand hole, surface uniformity. After these inspection, the fittings are of excellent quality.
Our fittings are provided with following different types
Connection type: Clamped, welded, threaded, flanged, etc
Specification: 1/2"-8", DN10-DN200, other sizes are provided according to customers' requirements
Material quality: SUS304, SUS316L
Polishing: Mirror polish, Matt polish
Standard: ISO, DIN, 3A, SMS, IDF, AS, BS4825...
Application: Pharmacy, beer, food, dairy, beverage, cosmetic, chemical industry



Manholes

The manhole covers are widely used in pressure tanks of food, brewing, beverage and paharmacy industries.

Materials: SUS304, SUS316L

Sealing of material: EMDM/SILICONE/NBR

SS handle/plastic handle

Surface treatment: Mirror polished, /Matte.

We can produce the following series of manholes

Round pressure manway :

Round non-pressure manway

Round manway with sight glass

oval pressure manway

oval non-pressure manway

rectangle manway with two interectant arms

rectangle manway with one interectant arms



Tank Fitting



Cleaning Ball



Filter



Sight Glass



Sanitary Centrifugal Pump

Our centrifugal pump is food grade pump which widely used for pharmaceutical,dairy,milk,beer, brewing, beverage industries.

Features:

- Motor:0.55-22Kw
- Impeller:Open type or closed type
- Rotating speed:2900rpm(50Hz)or 3600rpm(60Hz)
- Flow:1.5-120m³/h
- Lift:0-75m
- MAX pressure:10Bar
- MAX temperature:120°C /248°C
- Connection:Clamp,Thread,Flange, Welding
- Standard:DIN,SMS,3A,ISO,IDF,RJT
- And according to customers' requirements, we design movable type and explosion type.

Material:


- Motor housing:Cold rolled stainless steel plate
- Precision casting impeller:AISI 304/316L
- Contact parts with material:Viton,EPDM
- Gasket:SSC-Sic/EPDM
- Internal surface:Ra≤0.8um
- External surface:mirror polish



Rotor/Self-priming Pump



Rotor Pump



Self-priming Pump





Sanitary Pipe

HIGH-PRECISION SANITARY PIPE

Provide both welded and seamless sanitary pipes for food and beverage industries.

The sanitary pipes are smooth, non sand hole, precise, clean, good roundness.

Size: 1/2"-8"

Material: SS202, SS304, SS316L

Standard: DIN/ 3A/ SMS/ ISO

Surface: internal&external mirror/internal&external dull/internal mirror&external dull

Quality inspection items: 1 chemical property 2 extension test 3 Flattening test 4 hydraulic test 5 Flaring test 6 detection test

Internal Ra 0.3-0.4, External Ra0.6-0.8

Capped for both ends to prevent transportation damage



ISO/IDF			SMS-DS				3A			DIN11850	
Size	D	T(mm)	Size	D	T(mm)		Size	D	T(mm)	Size	T(mm)
					1	2					
1/2"	12.7	1.5/1	25	25	1.25	1.5	1/2"	12.7	1.65	12	1.5
3/4"	19.1	1.5/1	32	32	1.25	1.5	3/4"	19	1.65	18	1.5
1"	25.4	1.5/1.2	38	38	1.25	1.5	1"	25.4	1.65	22	1.5
1-1/4"	31.8	1.5/1.2	51	51	1.25	1.5	1-1/2"	38.1	1.65	28	1.5
1-1/2"	38.1	1.5/1.2	63.5	63.5	1.5	2.0	2"	50.8	1.65	34	1.5
45	45	2.0	76	76	1.6	2.0	2-1/2"	63.5	1.65	40	1.5
48	48	1.5	89	89	2.0	2.0	3"	76.2	1.65	52	1.5
2"	50.8	1.5	101.6	101.6	2.0	2.0	4"	101.6	2.1	70	2.0
57	57	2.0					6"	152.4	2.8	85	2.0
2-1/2"	63.5	2.0								104	2.0
3"	76.2	2.0								129	2.0
3-1/2"	89	2.0								154	2.0
4"	101.6	2.0								204	2.0
108	108	2.0								254	2.0
114.3	114.3	2.0									
133	133	3.0									
159	159	3.0									
204	204	2.0									

Pipe Materials

